

45mm 雙連滑動式可變電阻器製品規格書

45 mm 2 UNIT SLIDE POTENTIOMETERS SPECIFICATIONS

1. 一般事項 General

1.1 適用範圍：此規範適用於電子機器之可變電阻器。

Application: This specification is applied to potentiometers used for electronic equipment.

1.2 使用溫度範圍 Operating temperature: -10~+55°C

1.3 試驗狀態：若無特別規定限制，則以溫度5~35°C，相對濕度45~85%，氣壓860~1060mbar之標準狀態測之。
但對此標準狀態之測定值發生判定疑問或有特別要求則以基準狀態(溫度20±2°C,相對濕度
 $65 \pm 5\%$,氣壓860~1060mbar)為準測定。

Test conditions : the standard test conditions shall be 5~35°C in temperature ,45~85%RH
and 860~1060mbar in atmospheric , should any doubt arise in judgement ,
tests shall be conducted at $20 \pm 2^{\circ}\text{C}$, $65 \pm 5\%$ RH and 860~1060mbar .

2. 構造、尺寸 Construction and dimensions 依組立圖 Refer to attached drawing

3. 電氣性能 Electrical characteristics

NO.	項目 Item	試驗條件 Test conditions	規格 Specifications
3.1	全阻抗值 Total resistance	把柄置于端子1或3終端，測定端子1-3間的阻抗值 Measurement shall be made by the resistance between terminal 1 and 3 with lever setted at terminal 1 or 3 .	公稱全阻抗值 $\pm 20\%$ Nominal total resistance $\pm 20\%$
3.2	額定電力 Power rating	端子1和3間所能連續負荷之最大電力 Power rating is based on continuous full load operation at the maximum voltage between terminal 1 and terminal 3 .	B 特性曲線: 0.5W B taper: 0.5W 其它特性曲線: 0.25W Others : 0.25W
3.3	額定電壓 Rated voltage	額定電壓 Rated voltage $E=\sqrt{PR} (V)$ 額定電力 P: Power rating (W) 公稱全阻抗值 R: Nominal total resistance (Ω) 當額定電壓超過最高使用電壓的時候，最高使用電壓即為額定電壓。 When the rated voltage exceeds the maximum operating voltage , the maximum operating voltage shall be the rated voltage .	
3.4	殘留阻抗 Residual resistance	滑動子置于移動距離的兩末端時，端子1-2間，端子2-3間的阻抗值測定。 The resistances at each end of the mechanical between terminal 1 and 2, terminal 2 and 3 shall be measured .	1Ω 以下 (MAX)

					APPD.	CHKD.	DSGD.	DOCUMENT NO.:				
					周貴榮	周貴榮	鐘學峰	45RFK2-A-	-02-6H			
								VERSION :	A			
								PAGE:	1 OF 5			
SYMB	DATE	APPD	CHKD	DSGD	2007.9.27	2007.9.27	2007.9.27	Drawing NO:	45RF-001			

45 mm 雙連滑動式可變電阻器製品規格書

45 mm 2 UNIT SLIDE POTENTIOMETERS SPECIFICATIONS

NO.	項目 Item	試驗條件 Test conditions				規 格 Specifications
3.5	阻抗變化特性 Taper	電壓法測定 注*記號表示第3個端側開始滑動,且端子位 置2、3端子同側。 Measurement shall be made by the resistance law method. Note* Denotes terminal 3 as reference point, and terminal 2 and 3 is same side.				
		變化特性 taper	測定位置 test point (mm)	V1-2 V1-3	V2-3 V1-3	
		A	27	✓	—	15~30%
		B	22.5	✓	—	40~60%
		C	*27	—	✓	15~30%
		D	22.5	✓	—	2~15%
		K	22.5	✓	—	15~35%
		W	13.5±1	✓	—	5~15%
			22.5	✓	—	40~60%
			31.5	✓	—	85~95%
3.6	絕緣阻抗 Insulation resistance	施加500V之直流電壓,1分鐘後測試 測試位置：端子和外蓋間 端子和把柄間 Test voltage : 500V D.C measure after 1 min. Test position : Between terminal and frame. Between terminal and lever.				100MΩ 以上(MIN)
3.7	耐電壓 Voltage proof	以1000V之交流電壓,測試1分鐘 測試位置：端子和外蓋間 端子和把柄間 Applying 1000V A.C measure for 1 min. Applied position : Between terminal and frame. Between terminal and lever .				不可有損傷,電弧,絕緣破壞. Without damage to parts arcing or breakdown .
3.8	滑動雜音 Slider noise	端子1-3間印加直流電壓20V(額定電壓20V以下時,則 印加此額定電壓),以20mm/秒的移動速度所測定之 雜音。 Applying 20V D.C between the terminals 1 and 3 . (When the rated voltage is small than the 20V D.C, it shall be applied the rated voltage.) And then the noise shall be measured by the specified speed 20mm / SEC.				60mV以下 (MAX)

				APPD.	CHKD.	DSGD.	DOCUMENT NO.:
				周貴榮	周貴榮	鐘學峰	45RFK2-A- -02-6H
							VERSION : A
							PAGE: 2 OF 5
SYMB	DATE	APPD	CHKD	DSGD	2007.9.27	2007.9.27	Drawing NO: 45RF-001

45 mm 雙連滑動式可變電阻器製品規格書

45 mm 2 UNIT SLIDE POTENTIOMETERS SPECIFICATIONS

NO.	項目 Item	試驗條件 Test conditions	規格 Specifications
3.9	連動誤差 Tracking error	<p>在前,後段的1-3端子間加1KHz,2V的直流電壓, 以前段為基準,1-2端子間的輸出偏差. 注:(C變化特性測2-3端子間的輸出)</p> <p>測試位置:阻抗變化特性的測定點 W特性測移動距離50%的位置 .</p> <p>Applying 2V D.C(1KHz) across terminals 1 and 3 of the front and rear section , output across terminals 1 and 2 of the rear section of the front section output level .</p> <p>Notes : (taper C output across terminals 2 and 3) . Measuring position: At taper measuring point. W at 50% of lever travel .</p>	± 2dB

4. 機械性能 Mechanical characteristic

4.1	把柄移動距離 Lever travel		45±1mm
4.2	動作力 Operating force	<p>移動速度 : 20mm/秒 操作位置 : 把柄前端5mm處 Traveling speed : 20mm / SEC . Operating position : 5mm from lever end .</p>	60gf以下 (MAX)
4.3	把柄止動強度 Lever travel stop strength	<p>把柄置于兩末端,外框上面起5mm位置施加5Kgf靜負荷 10秒鐘 .</p> <p>A static load of 5Kgf shall be applied at the point 5mm form top surface of the case for both ends in the direction of lever travel for 10 SEC .</p>	不可產生接觸不良和明顯之松動 Without excessive play or poor contact .
4.4	把柄偏心 Lever deviation	<p>相對於螺絲孔中心,測定把柄中心到螺絲孔中心的距離 After sliding lever as far as it will go in each direction, the distance from the center of the lever to the middle of the mounting screw hole shall be measured at the both ends .</p>	單側0.5mm 以下 0.5mm MAX on each end

					APPD.	CHKD.	DSGD.	DOCUMENT NO.:	
								45RFK2-A-	-02-6H
SYMB	DATE	APPD	CHKD	DSGD	周貴榮	周貴榮	鐘學峰	VERSION :	A
								PAGE:	3 OF 5
								Drawing NO:	45RF-001
SYMB	DATE	APPD	CHKD	DSGD	2007.9.27	2007.9.27	2007.9.27		

滑動式可變電阻器規格書

SLIDE POTENTIOMETERS SPECIFICATIONS

NO.	項目 Item	試驗條件 Test conditions	規格 Specifications
4.5	把柄擠壓 引張強度 Thrust and tensile lever	把柄的擠壓方向和引張方向施加10Kgf靜負荷 10秒鐘。 Thrust and tensile static load of 10Kgf shall be applied to the potentiometer in the lever direction for 10 SEC .	不可產生破損, 滑動不平順, 電氣性能需滿足。 Without damage such as bed sliding and breaking or play in the lever , Electrical characteristics shall be satisfied.
4.6	把柄橫振幅 Displacement of Lever	在把柄移動方向的垂直方向施加250gf-cm, 在把柄的前端測定。 A torsion moment of 250gf-cm shall be applied at the Lever in a direction perpendicular to the axial direction and then the displacement shall be measured.	2 (2 × L/25) mm p-p 以下 L = 把柄長度 2 (2 × L/25) mm p-p MAX L = Length of lever
4.7	焊錫耐熱性 Resistance to soldering heat	請參照DIP焊錫件 (see 5 of 5). Condition of DIP soldering (see 5 of 5).	全阻抗值變化在初期的±5%以內。 端子不可有接觸不良或明顯松動。 Change in total resistance is relative to the value before test ±5% . Without excessive looseness of terminals and failure contact

5. 耐久性能 Endurance

5.1	滑動壽命 Sliding life	無負荷狀態, 把柄滑動速度600回/小時, 有效回移動距離的90%以上, 總次數100,000回以上。 The moving contact, without electrical load, shall be slided from one end stop to the other end returned to its original position extend over 90% or more effective distance. Slide speed : 600 cycle / hour . Total cycles : 100,000 cycles .	1. 全阻抗值的變化為初期值±15%以內。 2. 滑動雜音:150mV 以下 3. 其它需滿足(3項) (4項) 1. Change in total resistance is relative to the value before test ±15% . 2. Noise : 150mV MAX 3. Clause (3) (4) shall be satisfied .
-----	----------------------	---	---

SYMB	DATE	APPD	CHKD	DSGD	APPD.	CHKD.	DSGD.	DOCUMENT NO.:			
								周貴榮	周貴榮	鐘學峰	45RFK2-A- -02-6H
											VERSION : A
											PAGE: 4 OF 5
											Drawing NO: 45RF-001
SYMB	DATE	APPD	CHKD	DSGD	2007.9.27	2007.9.27	2007.9.27				

滑動式可變電阻器規格書


SLIDE POTENTIOMETERS SPECIFICATIONS

DIP焊錫條件

Condition of DIP soldering :

1. 浸漬焊錫處理時, 請確保在下列條件下作業:

Soldering shall be certified with following condition.

1.1	使用基板 Substrate to be soldered	t1.6厚單面銅箔積層板 Copper clad clad laminated phenol board in one surface of 1.6mm thickness.
1.2	助焊劑比重 Specific gravity of flux	0.82±0.01(發泡式). 0.82±0.01(foaming type).
1.3	助焊劑高度 Height of flux	發泡面高度接觸到基板下面, 不可流入基板表面. Just under PCB.AS shown. 
1.4	預熱溫度 Preheat temperature	(印刷基板之RV固定面溫度)100°C 以下, 2分鐘以內 (Surface temperature of mounting side)100°C MAX within 2 MIN.
1.5	焊錫溫度 Solder temperature	260°C±5°C,5秒以內. 260°C±5°C,Within 5 SEC.
	手焊溫度 Manual solder temperature	350°C±5°C,3秒以內. 350°C±5°C,Within 3 SEC.

2. 以上工程1回通過即可.

Please use the above process only one times.

RoHS Compliance

					APPD.	CHKD.	DSGD.	DOCUMENT NO.:	
								45RFK2-A-	-02-6H
					周貴榮	周貴榮	鐘學峰	VERSION :	A
								PAGE:	5 OF 5
SYMB	DATE	APPD	CHKD	DSGD	2007.9.27	2007.9.27	2007.9.27	Drawing NO:	45RF-001